ZELLER+GMELIN



Divinol ATF-C Premium VI

Clear premium ATF gear oil Dexron VI

ARTICLE DESCRIPTION

Divinol ATF-C Premium VI is a clear power transmission oil for automatic transmissions and has the following properties:

- Excellent oxidation stability
- Very good wear protection
- Excellent cold flow behavior
- Wide temperature application range
- Good sealing compatibility
- Excellent shear stability
- for extended oil change intervals
- universally applicable ATF
- can also be used in **hybrid vehicles**.

TYPICAL KEY FIGURES

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eislingen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de - Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited partnership Registered office Eislingen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH - Registered office Eislingen - Local Court Ulm HRB 530641

Colour / DIN ISO 2049	L 2.0
Appearance	brown, clear
Density/15°C / DIN EN ISO 12185	0.85
Viscosity/40°C / ASTM D 7042	34 mm²/s
Viscosity/100°C / ASTM D 7042	6.9 mm²/s
Viscosity index / ASTM D 2270	160
Flash point (Cleveland) / DIN ISO 2592	222 °C
Pour point / ASTM D 7346	-51

SPECIFICATION

GM Dexron VI*; GM Dexron III G/H; GM Dexron II D; GM Dexron TASA; Ford Mercon V; JASO 1 A

DIVINOL RECOMMENDATION

Allison C4 / TES 295 / TES 389/ TES 468; BMW / MINI P/N 81 22 9 400 272/275; BMW / MINI P/N 81 22 9 407 858/859; BMW / MINI P/N 83 22 0 024 249/359; BMW / MINI P/N 83 22 0 026 922; BMW / MINI P/N 83 22 0 402 413; BMW / MINI P/N 83 22 0 403 248; BMW / MINI P/N 83 22 0 403 249; BMW / MINI P/N 83 22 7 542 290; BMW / MINI P/N 83 22 9 407 765; BMW / MINI P/N 83 22 9 407 807; DTFR 13C150; DTFR 13C160; DTFR 13C170; DTFR 13C180; MB 236.3/236.5/236.6/236.7/236.8/236.9/236.10/236.11/236.41/236.81/236.91; MAN 339A / 339D / 339F / 339 L1 / 339 V1/V2 / 339 Z2/Z3; Chrysler ATF +/+2/+3/+4; Honda ATF- Z1; ZF 5 Speed (S671090 170); ZF 6 Speed (S671 090 255); Suzuki 3314; Suzuki 3317; JWS 3309; Voith 55.6336.XX (G13636); Voith 55.6335.XX (G607); Isuzu ATF III; Isuzu P/N 08200-9001; PSA Peugeot Citroën P/N Z 000169756; Renault Matic D2; Saab 3309 – T-IV; SSANG YONG DSIH 5M-66; Porsche P/N 000 043 204 41; Porsche P/N 000 043 204 63; Porsche P/N 000 043 210 54; Porsche P/N 000 043 305 42; Porsche P/N 999 917 547 00; Porsche P/N 958 300 901 00; Idemitsu K17; ATF HP; Jaguar JLM 20238; Jaguar JLM 21044; Jaguar K17; Jaguar WSSM2C922-A1; Stellantis 68218925AB; Hyundai/Kia SP-II / III; Iveco 500042124; Mazda ATF

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eislingen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de - Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited partnership Registered office Eislingen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH - Registered office Eislingen - Local Court Ulm HRB 530641

M III; Mazda ATF M V; Mazda Type T-IV; Mazda F-1; Mitsubishi ATF-J2; Mitsubishi SP, P/N MS991156; Mitsubishi SP-II; Mitsubishi SP-III; Nissan / Infinity N402, Matic D/J/K; Toyota/Lexus / Scion D-II /T-III/IV; Subaru ATF HP, Subaru P/N K0140Y0700; Volvo P/N 1161521; Volvo P/N 1161540; Volvo 6 Speed (P/N 31256774 & 31246675); Volvo CE 97340; Volvo CE 97341; Volvo CE 97342; VW G 052 025 / G 052 162 / VW G 052 540 / G 052 990 / G 055 025 / G US 000 162; ZF TE-ML 03D / 03M / 05L / 09 / 11A / 11B / 14B / 14C / 21L

*Viscosity requirement is not met

USE / APPLICATION

Divinol ATF-C Premium VI is used as power transmission oil in automatic transmissions of cars, trucks, buses and special vehicles. It can also be used in hydrodynamic converters, hydraulic systems and power steering systems in accordance with the manufacturer’s instructions.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eislingen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de - Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited partnership Registered office Eislingen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH - Registered office Eislingen - Local Court Ulm HRB 530641