ZELLER+GMELIN



TECHNICAL DATA SHEET

Divinol ATF Premium VI LV

Low-viscosity, red premium ATF oil Dexron VI

ARTICLE DESCRIPTION

Divinol ATF Premium VI LV is an automatic transmission oil with reduced viscosity (LV = Low Viscosity applications), which enables fuel savings. High-quality additive components in combination with high-quality base oils make it possible to produce thinner automatic transmission oils that combine the requirements of modern transmission technology with ecological/economic considerations.

The excellent temperature properties enable versatile use and therefore optimum operating conditions at high and low temperatures. Optimum shifting, very good ageing and oxidation stability as well as long oil change intervals are ensured by the use of synthetic technology oils, among other things.

Advantages:

- Excellent oxidation stability
- Very good wear protection
- Excellent cold flow behavior
- Wide temperature application range
- Good sealing compatibility

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eislingen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de - Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited partnership Registered office Eislingen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH - Registered office Eislingen - Local Court Ulm HRB 530641

ZELLER+GMELIN

- Excellent shear stability
- for extended oil change intervals
- ATF for LV applications
- can also be used in **hybrid vehicles**

TYPICAL KEY FIGURES

Appearance	red
Density/15°C / DIN EN ISO 12185	0.85 g/cm³
Viscosity/40°C / ASTM D 7042	29 mm²/s
Viscosity/100°C / ASTM D 7042	6 mm²/s
Viscosity index / ASTM D 2270	155
Flash point (Cleveland) / DIN ISO 2592	210 °C
Pour point / ASTM D 7346	-45 °C

SPECIFICATION

Dexron VI; Dexron HP; Mercon LV; JASO 1-A; JASO 1-A-LV

DIVINOL RECOMMENDATION

MB 236.12/.14/.15./41; MB 236.82; VW G 052 162; VW G 055 005; VW G 055 162; VW G 055 540; VW G 060 162; BMW 83 22 2 305 397; BMW 83 2 22 152 426; BMW 83 22 0 142 516; BMW 83 22 2 355 599; BMW 83 22 2 289 720; BMW M-1375.4; Porsche P/N 000 043 304 00/01; Porsche P/N 000 043 305 43; Porsche P/N 000 043 305 54; Porsche P/N 000 043 306 24; Porsche P/N 958 300 540 00; Chrysler 68043742AA; Toyota WS; Nissan Matic-S; Nissan Matic-W; Mitsubishi SP-IV; Mitsubishi Dia Queen ATF-PA; Mitsubishi ATF-J3; Fiat 9.55550-AV5; Hyundai/KIA SP-IV; Hyundai/KIA SPH-IV; Hyundai SP-IV M; Hyundai/Kia SP-IV RR; Hyundai NWS-9638; Honda DW-1; Honda Type 3 & 3.1; JWS 3324; Aisin Warner AW-1; Saab 93 165 147 AW1; Bentley JNV 862 564; Mazda ATF FZ; Mazda ATF 3.1; Jaguar 02JDE26444; Land Rover

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eislingen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de - Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited partnership Registered office Eislingen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH - Registered office Eislingen - Local Court Ulm HRB 530641

LR023288; ZF 6 Speed (S671 090 255); ZF 8 Speed (S671 090 312); Volvo P/N 31256774 ; Volvo 31246675

USE / APPLICATION

Divinol ATF Premium VI LV is used as power transmission oil in automatic transmissions of passenger cars, light commercial vehicles and special vehicles.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eislingen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de - Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited partnership Registered office Eislingen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH - Registered office Eislingen - Local Court Ulm HRB 530641