



Divinol ATF Premium VI

Red premium ATF oil Dexron VI

PRODUCT DESCRIPTION

Divinol ATF Premium VI is a red-colored transmission fluid for automatic transmissions and has the following properties:

- + excellent oxidation stability
- + very good wear protection
- + excellent low-temperature flow properties
- + wide operating temperature range
- + good seal compatibility
- + Outstanding shear stability
- + For extended oil change intervals
- + universally applicable ATF
- + Can also be used in **hybrid vehicles**.

KEY METRICS

Appearance	Red
Density/15°C / DIN EN ISO 12185	0.85 g/cm ³
Viscosity/40°C / ASTM D 7042	34 mm ² /s
Viscosity/100°C / ASTM D 7042	6.9 mm ² /s
Viscosity index / ASTM D 2270	160
Flash point (according to Cleveland) / DIN ISO 2592	222 °C
Pour point / ASTM D 7346	- 51 °C

SPECIFICATIONS

GM Dexron VI*; GM Dexron III G/H; GM Dexron II D; GM Dexron TASA; Ford Mercon V*; JASO 1 A



DIVINOL RECOMMENDATION

Allison C4 / TES 295 / TES 389 / TES 468; BMW / MINI P/N 81 22 9 400 272/275; BMW / MINI P/N 81 22 9 407 858/859; BMW / MINI P/N 83 22 0 024 249/359; BMW / MINI P/N 83 22 0 026 922; BMW / MINI P/N 83 22 0 402 413; BMW / MINI P/N 83 22 0 403 248; BMW / MINI P/N 83 22 0 403 249; BMW / MINI P/N 83 22 7 542 290; BMW / MINI P/N 83 22 9 407 765; BMW / MINI P/N 83 22 9 407 807; DTFR 13C150; DTFR 13C160; DTFR 13C170; DTFR 13C180; MB 236.3/236.5/236.6/236.7/236.8/236.9/236.10/236.11/236.41/236.81/236.91; MAN 339A / 339D / 339F / 339 L1 / 339 V1/V2 / 339 Z2/Z3; Chrysler ATF +/+2/+3/+4; Honda ATF- Z1; ZF 5-speed (S671090 170); ZF 6-speed (S671 090 255); Suzuki 3314; Suzuki 3317; JWS 3309; Voith 55.6336.XX (G13636); Voith 55.6335.XX (G607); Isuzu ATF III; Isuzu P/N 08200-9001; PSA Peugeot Citroën P/N Z 000169756; Renault Matic D2; Saab 3309 - T-IV; SsangYong DSIH 5M-66; Porsche P/N 000 043 204 41; Porsche P/N 000 043 204 63; Porsche P/N 000 043 210 54; Porsche P/N 000 043 305 42; Porsche P/N 999 917 547 00; Porsche P/N 958 300 901 00; Idemitsu K17; ATF HP; Jaguar JLM 20238; Jaguar JLM 21044; Jaguar K17; Jaguar WSSM2C922-A1; Stellantis 68218925AB; Hyundai/Kia SP-II / III / IV; Iveco 500042124; Mazda ATF M III; Mazda ATF M V; Mazda Type T-IV; Mazda F-1; Mitsubishi ATF-J2; Mitsubishi SP, P/N MS991156; Mitsubishi SP-II; Mitsubishi SP-III; Nissan / Infinity N402, Matic D/J/K; Toyota/Lexus / Scion D-II / T-III/IV; Subaru ATF HP, Subaru P/N K0140Y0700; Volvo P/N 1161521; Volvo P/N 1161540; Volvo 6-Speed (P/N 31256774 & 31246675); Volvo CE 97340; Volvo CE 97341; Volvo CE 97342; VW G 052 025 / G 052 162 / VW G 052 540 / G 052 990 / G 055 025 / G US 000 162; ZF TE-ML 03D / 03M / 05L / 09 / 11A / 11B / 14B / 14C / 21L

*Viscosity requirement is not met (may be used for performance applications)

APPLICATION

Divinol ATF Premium VI It is used as a transmission fluid in automatic transmissions for passenger cars, trucks, buses, and specialty vehicles. It may also be used in torque converters, hydraulic systems, and power steering systems, in accordance with the manufacturer's specifications.

Take advantage of our service, we will be happy to advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.