ZELLER+GMELIN



TECHNICAL INFORMATION

Divinol ATF Special R

Red Dexron III H/G Automatic Transmission Fluid

PRODUCT DESCRIPTION

Divinol ATF Special R is a red-colored transmission fluid for automatic transmissions with a wide range of applications. This automatic transmission fluid offers optimal protection and friction characteristics thanks to the use of high-quality additives. In addition to modern additive technology, the base oil used also plays a key role in ensuring the longevity of transmissions. **Divinol ATF Special R** is manufactured using HC synthesis technology and high-quality base oils to ensure the best possible performance and usability of the fluid in your daily operations. Additionally, seal compatibility and performance reserves under extreme conditions are key factors that round out the product's technical performance.

Divinol ATF Special R It also features the following additional properties:

- Excellent oxidation stability
- Very good wear protection
- Excellent cold flow properties
- Wide operating temperature range
- High-quality corrosion protection

KEY METRICS

Appearance	red
Density/15°C / DIN EN ISO 12185	0.85 g/cm³
Viscosity/40°C / ASTM D 7042	34.8 mm²/s
Viscosity/100°C / ASTM D 7042	7.4 mm²/s
Viscosity index / ASTM D 2270	170
Flash point (according to Cleveland) / DIN ISO 2592	210 °C
Pour point / ASTM D 7346	-51 °C

SPECIFICATIONS

GM Dexron III H/G; GM Dexron II D; GM Dexron TASA; Ford Mercon 2004

APPROVALS

DTFR 13C170; Voith H55.6335.XX; ZF TE-ML 03D/04D/14A/17C (ZF009444)

DIVINOL RECOMMENDATION

Allison C-4; Ford ESP-M2C166-H; Ford ESP-M2C138-CJ; MAN 339 V1/Z1; MAN 339 A/D/F/L1&2; MB 235.1/2/5/6/7/9; Volvo 97340 / 97341 (AT101); JCB Standard 4000/2300; ZF-TE-ML 05L/09(Bosch)/11A/11B/21L

APPLICATION

Divinol ATF Special R is used as a transmission fluid in automatic transmissions for passenger cars, trucks, buses, and specialty vehicles. It can be used in torque converters (automatic transmissions), manual transmissions, hydraulic systems, power steering systems, and auxiliary drives, in accordance with the manufacturer’s specifications.

Take advantage of our service, we will be happy to advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eislingen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de - Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited partnership Registered office Eislingen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH - Registered office Eislingen - Local Court Ulm HRB 530641