TECHNICAL DATA SHEET

Divinol GL 4 80W-90

Mineral oil based gear oil GL-4 SAE 80W90

PRODUCT DESCRIPTION

High performance gear oil according API GL-4.

CHARACTERISTICS

SAE Grade	80W
Colour / Appearance	brown, clear
Density/15°C / DIN EN ISO 12185	0,885 g/cm³
Viscosity/40°C / ASTM D 7042	135 mm²/s
Viscosity/100°C / ASTM D 7042	14 mm²/s
Viscosity index / ASTM D 2270	110
Flash point (Cleveland) / DIN ISO 2592	>= 200 °C
Pour point / ASTM D 7346	-27 °C °C

SPECIFICATION

API GL-4

DIVINOL RECOMMENDATION

MAN 341 E2/Z2; DTFR 13B100; MB 235.1; ZF TE-ML 02B/06L/08/16A/17A

52110 01/2024-52110-14

The information contained in this document (the “Product Specification”) is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co. KG · Schlossstraße 20 · 73054 Eislingen/Fils · Germany · Postfach 13 65 · 73054 Eislingen/Fils
Phone: +49 7161 802-0 · Fax: +49 7161 802-290 · info@zeller-gmelin.de · Geschäftsführer: Dipl.-Ing. (FH) Siegfried Müller
Dipl.-Kfm. Walter Jerusalem · Dipl.-Ing. (FH) Thomas Alpers · Kommanditgesellschaft Sitz Eislingen · Amtsgericht Ulm HRA 530107
Persönlich haftende Gesellschafterin Zeller+Gmelin Verwaltungs GmbH · Sitz Eislingen · Amtsgericht Ulm HRB 530641

TECHNICAL DATA SHEET

Divinol GL 4 80W-90

Mineral oil based gear oil GL-4 SAE 80W90

APPLICATION

A high-performance, multi-purpose transmission oil for vehicle gearboxes and lightly loaded final drives, where API GL-4 can be filled.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

The information contained in this document (the “Product Specification”) is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co. KG · Schlossstraße 20 · 73054 Eislingen/Fils · Germany · Postfach 13 65 · 73054 Eislingen/Fils
Phone: +49 7161 802-0 · Fax: +49 7161 802-290 · info@zeller-gmelin.de · Geschäftsführer: Dipl.-Ing. (FH) Siegfried Müller
Dipl.-Kfm. Walter Jerusalem · Dipl.-Ing. (FH) Thomas Alpers · Kommanditgesellschaft Sitz Eislingen · Amtsgericht Ulm HRA 530107
Persönlich haftende Gesellschafterin Zeller+Gmelin Verwaltungs GmbH · Sitz Eislingen · Amtsgericht Ulm HRB 530641