



Divinol Multi-Fluid

Multipurpose Care and Maintenance Fluid

PRODUCT DESCRIPTION

Divinol Multi-Fluid is a high-performance product, free from resin and silicon, based on especially chosen aromatic-free basis oils and additives. This multifunctional care and maintenance fluid shows an excellent economic efficiency. It can be used all in one as lubricant, corrosion protecting oil, creep oil, oil for displacing humidity as well as cleaner. **Divinol Multi-Fluid** is an excellent product due to the following characteristics:

- + Protects all metals against corrosion, also under extreme conditions
- + Doesn't deposit, even after a long storage period
- + Stops screeching and creaking
- + Releases stuck connections
- + Releases rusted mechanical parts
- + Protects electrical contacts
- + Lubricates without sticking
- + Cleans most powerful dirt
- + Displaces humidity

1

CHARACTERISTICS

Composition	Synthetic hydrocarbons with special corrosion inhibitors as well as with product specific additives
Density/15°C / DIN EN ISO 12185	825 kg/m ³
Viscosity/20°C / ASTM D 7042	3.7 mm ² /s
Flash point (Pensky-Martens) / DIN EN ISO 2719	> 61 °C
Condensation atmosphere (AHT) / DIN EN ISO 6270-2	39 cycles
Salt spray test / DIN EN ISO 9227	40 Std.
Odour	mild



DIVINOL RECOMMENDATION

Divinol Multi-Fluid fulfills Daimler DBL 6772

APPLICATION

Corrosion protection: When using **Divinol Multi-Fluid**, the length of the protection period depends on the material which has to be protected and on the environmental conditions. Under normal circumstances, the following protection effect can be expected for steel:

1. Covered or inside more than 1 year 2. Outside, but protected min. 6 months up to 1 year 3. Normal outside conditions min. 30 days up to 60 days 4. Extreme outside conditions min. 15 days up to 30 days (next to the coast, in case of high air humidity etc.)

For protection which has to last longer, **Divinol Multi-Fluid** should be applied repeatedly. Between 60 and 90 minutes, depending on the room temperature.

Typical usage ranges are the following sectors: automobile, office, electronics, household, industry, tool and engineering industry, agriculture, navigation, sports devices, guns etc. **Divinol Multi-Fluid** can simply be applied onto the affected parts. The remaining very thin film doesn't dry and is compatible with lacquer, plastic, and rubber. The parts can be sprayed with Divinol MULTI-FLUID while they are wet, as the product displaces humidity very fast.

Take advantage of our service, we will be happy to advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.