



Divinol Multilight 10W-40

Top-class multigrade oil SAE 10W-40

ARTICLE DESCRIPTION

Modern low-friction engine oil for gasoline and diesel engines in cars, formulated based on high-quality base oils. This engine oil is suitable for use in modern car engines with and without turbochargers, even under difficult operating conditions. By using selected additives, special raffinates and base oil from HC synthesis technology, deposits are reduced and sludge is prevented. High alkaline reserves ensure good corrosion protection properties. A modern formulation concept results in fuel savings and a reduction in oil consumption. Also suitable for motorcycles according to the JASO MA standard. Please stick to manufacturer's instructions!

1

TYPICAL KEY FIGURES

Colour / DIN ISO 2049	3.5
SAE Grade	10W-40
Density/15°C / DIN EN ISO 12185	0.86 g/cm ³
Ash / Sulfate DIN 51575	1.2
Viscosity/40°C / ASTM D 7042	90 mm ² /s
Viscosity/100°C / ASTM D 7042	13.5 mm ² /s
Viscosity index / ASTM D 2270	160
Flash point (Cleveland) / DIN ISO 2592	230 °C
Pour point / ASTM D 7346	-36 °C
TBN	10 mgKOH/g



SPECIFICATION

API SN/CF; ACEA A3/B4; JASO MA

MANUFACTURER APPROVALS

Meet MB 229.1H specification

DIVINOL RECOMMENDATION

MB 229.3; VW 501.01/505.00; VW 502.00/505.00; PSA B71 2294; PSA B71 2292; PSA B71 2300; Renault RN 0700/0710; FIAT 9.55535-G2

USE / APPLICATION

Multi-purpose motor oil for all Otto and Diesel engines with or without turbo charger.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.