



Divinol Multilight FO 2 5W-30

Suitable for Ford and other engines

PRODUCT DESCRIPTION

Divinol Multilight FO 2 5W-30 is a special HC synthetic oil for modern Ford gasoline and diesel engines. This high-quality engine oil ensures rapid oil circulation, especially during startup and warm-up. Compliance with the Ford WSS M2C 913D specification ensures, in particular, greater fuel economy.

CHARACTERISTICS

Appearance	L 3.0
SAE Grade	5W-30
Density/15°C / DIN EN ISO 12185	0.85 g/cm ³
Viscosity/40°C / ASTM D 7042	58 mm ² /s
Viscosity/100°C / ASTM D 7042	10.2 mm ² /s
Viscosity index / ASTM D 2270	167
Flash point (Cleveland) / DIN ISO 2592	235°C
Pour point / ASTM D 7346	-45°C
TBN	8.5 mgKOH/g

SPECIFICATIONS

API SL; ACEA A5/B5

APPROVALS

Ford WSS-M2C-913-D; VWC 53036



DIVINOL RECOMMENDATION

Ford WSS-M2C-913-A; Ford WSS-M2C-913-B; Ford WSS-M2C-913-C; Ford WSS-M2C-925-A;
Renault RN 0700; STJLR.03.5003

APPLICATION

Divinol Multilight FO 2 5W-30 Recommended for gasoline and diesel engines in accordance with the respective manufacturers' specifications. Especially for Ford vehicles.

Take advantage of our service, we will be happy to advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.