



Divinol Multimax Advanced 5W-30

Latest generation low ash commercial vehicle oil SAE 5W-30 – ideal for reducing the number of oil types

ARTICLE DESCRIPTION

Divinol Multimax Advanced 5W-30 is a MHPD (Maximum High Performance Diesel) low-friction oil with the highest quality protective properties for the most modern truck diesel engines. The oil was specially developed for low-emission LOW SAPS EURO-V and EURO-VI engines. This engine oil is therefore suitable for all NOx reduction systems and particulate filters in combination with low-sulphur diesel (max. 50 ppm). Commercial vehicles with EGR, SCR and diesel particulate filters in particular require an oil of the quality **Divinol Multimax Advanced 5W-30**. In addition, **Divinol Multimax Advanced 5W-30** can also be used in older commercial vehicles without any problems and thus offers the possibility of reducing the grade.

Advantages:

- + Very good protection against oil deposits on pistons
- + High oxidation resistance
- + Fuel savings and therefore favorable economic conditions
- + Low oil consumption due to lower evaporation loss
- + offers extended oil change intervals (depending on manufacturer's instructions)

TYPICAL KEY FIGURES

Colour / DIN ISO 2049	4
SAE Grade	5W30
Density/15°C / DIN EN ISO 12185	0.856 g/cm ³
Ash / Sulfate DIN 51575	0.9



Viscosity/40°C / ASTM D 7042	65 mm ² /s
Viscosity/100°C / ASTM D 7042	11.3 mm ² /s
Viscosity index / ASTM D 2270	170
Flash point (Cleveland) / DIN ISO 2592	216 °C
Pour point / ASTM D 7346	-35 °C
TBN	11.5 mgKOH/g

SPECIFICATION

API CK-4; ACEA E11/E8/E9/E6; JASO DH-2

MANUFACTURER APPROVALS

DTFR 15C110; MAN 3677; Volvo VDS 4.5; Renault RLD-3; Mack EOS-4.5; Deutz DQC IV-18 LA

Meet Scania LDF-4 specification

Meet Caterpillar ECF-3 specification (self-certifying)

Meet MAN 3477; MAN 3275-1 specification (all obsolete)

DIVINOL RECOMMENDATION

DTFR 15C120; DTFR 15C100; DTFR 13D110; MB 228.51; MB 228.52; MB 228.31; MB 235.28; MAN 3777; DAF PSQL 2.4 LD; DAF PSQL 2.4; DAF PSQL 2.1E-LD; DAF PSQL 2.1E; Iveco 18-1804 TLS E6; Iveco 18-1804 TLS E9; Volvo CNG; Detroit Diesel DDC93K222; Voith Oil Class B; Cummins CES 20086; Ford WSS-M2C 213 -A1; Liebherr LH-00-ENG LA

USE / APPLICATION

Divinol Multimax Advanced 5W-30 is recommended for heavy-duty diesel engines, including turbochargers and exhaust aftertreatment systems, in compliance with the respective manufacturer's instructions for the longest oil change intervals.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.