



Divinol Multimax Extra 10W-40

High-quality commercial vehicle/fleet oil SAE 10W-40

ARTICLE DESCRIPTION

Semi-synthetic SHPD low-friction oil with fuel-saving properties, designed for heavy-duty diesel engines with medium sulfate ash content. The selection of base oils in combination with high-quality additives enables a high level of performance and prevents mirror surface formation in the engine. Divinol Multimax Extra 10W-40 is suitable for commercial vehicles, agricultural and construction machinery, and passenger cars/LCVs.

Advantages:

- + High-quality additives
- + Prevents technical problems such as deposits and coking in the engine
- + High-quality aging protection in the oil
- + Optimal lubrication in warm and cold seasons
- + Hardly any oil consumption
- + Suitable for rationalizing varieties and as fleet oil

TYPICAL KEY FIGURES

Colour / DIN ISO 2049	4.5
Appearance	brown, clear
SAE Grade	10W-40
Density/15°C / DIN EN ISO 12185	0.872 g/cm ³
Ash / Sulfate DIN 51575	1.4

49640

02/2026-49640-36

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eisligen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de - Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited partnership Registered office Eisligen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH - Registered office Eisligen - Local Court Ulm HRB 530641



Viscosity/40°C / ASTM D 7042	100 mm ² /s
Viscosity/100°C / ASTM D 7042	14.5 mm ² /s
Viscosity index / ASTM D 2270	148
Flash point (Cleveland) / DIN ISO 2592	214 °C
Pour point / ASTM D 7346	- 39°C
TBN	12 mgKOH/g

SPECIFICATION

ACEA E7/A3/B4; API CI-4/SL; Global DHD-1; Jaso DH-1

MANUFACTURER APPROVALS

Volvo VDS III; Renault RLD-2; MACK EO-N

Meet Caterpillar ECF-1A specification (self-certifying)

Meets MAN 3275 specification (obsolete)

DIVINOL RECOMMENDATION

DTFR 15B110; DTFR 13D110; DTFR 13D100; MB 228.3; 235.28; 235.27; Deutz DQC III-18; Cummins CES 20076, 20077, 20078; MTU Type 2; Scania LDF; Valtra CR

USE / APPLICATION

SHPD engine oil with smooth-running properties, especially for highly supercharged commercial vehicle diesel engines (turbochargers) and gasoline engines without particulate filters. Divinol Multimax Extra 10W-40 is a versatile lubricant that enables a long engine service life thanks to its good viscosity-temperature behavior and low friction values. Divinol Multimax Extra 10W-40 can also be used in gasoline and diesel passenger car/LCV engines without particulate filters, enabling its widespread use in vehicle fleets.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.