ZELLER+GMELIN



TECHNICAL INFORMATION

Divinol Multimax HD C3 15W-40

Mixed Fleet Engine Oil SAE 15W40

PRODUCT DESCRIPTION

Divinol Multimax HD C3 15W-40 is an SHPD multigrade oil suitable for the entire vehicle fleet. Excellent cleaning and sludge-carrying capacity (dispersant and detergent properties) allow for longer oil change intervals (depending on the manufacturer's specifications!). The oil simplifies inventory management in a mixed fleet thanks to its universal, year-round usability in both diesel and gasoline engines.

CHARACTERISTICS

SAE Grade	15W40
Density/15°C / DIN EN ISO 12185	0.870 g/cm³
Viscosity/40°C / ASTM D 7042	119 mm²/s
Viscosity/100°C / ASTM D 7042	16 mm²/s
Viscosity index / ASTM D 2270	144
Flash point (Cleveland) / DIN ISO 2592	230°C
Pour point / ASTM D 7346	-33 °C
TBN	11 mgKOH/g

SPECIFICATIONS

API CH-4/SJ; ACEA E3

APPROVALS

Meets MAN 3275 specifications (obsolete)
Meets Caterpillar ECF-1A specifications (self-certifying)

DIVINOL RECOMMENDATION

DTFR 15B110; MB 228.3; MB 228.1; Allison C-4; Deutz DQC-II; Caterpillar TO-2; Renault RLD; Volvo VDS; MTU Type 2; MACK EO-M+; Cummins CES 20077; Valtra E; NH 330G; VW 501.01/ 505.00; ZF-TE-ML 03A/07D

APPLICATION

For highly compressed, high-speed diesel engines in commercial vehicles, construction equipment, and agricultural machinery operating continuously in environments exposed to dirt, dust, heat, and cold. Suitable for gasoline and diesel engines.

Take advantage of our service, we will be happy to advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co. KG · Schlossstraße 20 · 73054 Eislingen/Fils · Germany · Phone: +49 7161 802-0 · info@zeller-gmelin.de · Managing Directors: Thomas Alpers, Dipl.-Ing. (FH) · Alexandra Scaglione, Dipl.-Betriebsw. (FH) · Dirk Eisele, Dr. rer. nat. · Tillmann Gehring, Dipl.-Ing. (FH), LL.M. · Limited Partnership, registered office in Eislingen · Ulm Local Court, HRA 530107 · General Partner: Zeller Gmelin Verwaltungs GmbH · Registered office in Eislingen · Ulm Local Court, HRB 530641