



Divinol Multimax High Tech 10W-30

Low ash high performance oil for Euro V and VI SAE 10W30

ARTICLE DESCRIPTION

Divinol Multimax High Tech 10W-30 is a modern, low saps motor oil with high quality protective properties for latest heavy duty diesel engines. The oil was developed specifically for low-emission LOW SAPS EURO V and EURO VI engines. Thus, this motor oil is for NOx and diesel particulate filter in combination with low sulfur containing diesel (max. 50 ppm). In particular, commercial vehicles with EGR, SCR and diesel particulate filters require an oil quality according Divinol Multimax High Tech 10W-30. In addition, Divinol Multimax High Tech 10W-30 easily be used in older vehicles and offers the possibility of oil stock reduction. Divinol Multimax High Tech 10W-30 fullfills the latest requirements for API CK-4 and Volvo VDS 4.5.

Advantages:

- + highly alloyed against oxidation and aging
- + top wear protection
- + optimal soot and sludge protection
- + very stable viscosity - temperatur behaviour
- + high shear stability
- + low oil consumption during work
- + perfectly suitable for fleet use

TYPICAL KEY FIGURES

Colour / DIN ISO 2049	4.5
SAE Grade	10W-30
Density/15°C / DIN EN ISO 12185	0.87 g/cm ³

49880

03/2026-49880-20

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eisligen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de - Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited partnership Registered office Eisligen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH - Registered office Eisligen - Local Court Ulm HRB 530641



Viscosity/40°C / ASTM D 7042	83 mm ² /s
Viscosity/100°C / ASTM D 7042	11.9 mm ² /s
Viscosity index / ASTM D 2270	142
Flash point (Cleveland) / DIN ISO 2592	230 °C
Pour point / ASTM D 7346	-36 °C
TBN	10.3 mgKOH/g

SPECIFICATION

API CK-4/SN; API CJ-4/SN; ACEA E11/E9/E7; JASO DH-1; JASO DH-2

MANUFACTURER APPROVALS

Volvo VDS 4.5; Renault RLD-3; Mack EOS 4.5; Deutz DQC III-18 LA

Meets Caterpillar ECF-3 specification (self-certifying)

DIVINOL RECOMMENDATION

DTFR 15C100; MB 228.31; MAN 3275; MAN 3575; MAN 3775; Ford WSS-M2C 171-F1; John Deere JDQ-78X; MTU 2.1; DDC 93K222 (Detroit Diesel); Cummins CES 20086; DAF PSQL 2.1E

USE / APPLICATION

Divinol Multimax High Tech 10W-30 is recommended for heavy-duty diesel truck, construction and agriculture engines, including turbochargers and catalysts for longest oil drain intervals. Stick to manufacturer's instructions.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.