



Divinol Multimax Plus 10W-40

High-quality low ash commercial vehicle engine oil SAE 10W40

ARTICLE DESCRIPTION

Divinol Multimax Plus 10W-40 is a MHPD diesel engine oil (Maximum High Performance Diesel) based on HC synthesis technology with excellent cold start behavior, which reduces engine wear. **Divinol Multimax Plus 10W-40** has been formulated and adapted for modern EURO level diesel engines with diesel particulate filters (DPF) or exhaust gas recirculation (EGR) and the use of diesel with a low sulphur content < 50 ppm. Extended oil change intervals are possible even under the toughest operating conditions in the commercial vehicle sector if the manufacturer's specifications are adhered to. Also suitable for diesel CNG/LNG engines in accordance with the manufacturer's instructions!

TYPICAL KEY FIGURES

Colour / DIN ISO 2049	4.5
Appearance	light brown, clear
SAE Grade	10W-40
Density/15°C / DIN EN ISO 12185	0.860 g/cm ³
Ash / Sulfate DIN 51575	0.9
Viscosity/40°C / ASTM D 7042	92 mm ² /s

49750

12/2025-49750-49

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eisingen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de
 - Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited
 partnership Registered office Eisingen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH -
 Registered office Eisingen - Local Court Ulm HRB 530641



Viscosity/100°C / ASTM D 7042	13.7 mm ² /s
Viscosity index / ASTM D 2270	150
Flash point (Cleveland) / DIN ISO 2592	245 °C
Pour point / ASTM D 7346	-39 °C
TBN	10 mgKOH/g

SPECIFICATION

API CJ-4; ACEA E8/E7/E6; JASO DH-2

MANUFACTURER APPROVALS

DTFR15C110; Volvo VDS-4.5; Renault RLD-3; MACK EOS-4.5; Deutz DQC IV-18-LA

Meet MAN 3477; MAN 3271-1 specification

Meet Caterpillar ECF-1A/ ECF 2 specification

DIVINOL RECOMMENDATION

DTFR 15C100; DTFR 13D100; MB 228.51; MB 228.31; MB 235.27; MB 226.9; CNH MAT 3521; Scania LDF-LA; DAF HP 2/ LA; Renault Truck RXD, Cummins CES 20076/20077; MTU Type 3.1

USE / APPLICATION

Divinol Multimax Plus 10W-40 is recommended for heavy-duty diesel truck engines, including turbochargers and particulate filters/catalytic converters for the latest emission standards and longer oil change intervals in compliance with the respective manufacturer's specifications.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49750

12/2025-49750-49

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eisingen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de
- Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited
partnership Registered office Eisingen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH -
Registered office Eisingen - Local Court Ulm HRB 530641