



Divinol Multimax Top 15W-40

High-quality commercial vehicle/fleet oil SAE 15W-40

ARTICLE DESCRIPTION

Divinol Multimax Top 15W-40 is specifically designed for heavy duty, high performance diesel engines. The high additive amount guarantees low friction, long engine life and therefore trouble-free engine operation under extreme conditions. Furthermore longer oil drain intervals in diesel engines are possible (depending on manufacturer's instructions). **Divinol Multimax Top 15W-40** provides optimum engine cleanliness, even under the most difficult conditions. Note: Do not use in Detroit- or GM-Allison two stroke Diesel engines.

Advantages:

- + very good protection against piston deposits
- + effective oxidation resistance
- + low oil consumption due to lower evaporation loss
- + robust oil film under high pressure and temperature

TYPICAL KEY FIGURES

Appearance	brown, clear
SAE Grade	15W-40
Density/15°C / DIN EN ISO 12185	0.873 g/cm ³
Ash / Sulfate DIN 51575	1.4
Viscosity/40°C / ASTM D 7042	92 mm ² /s
Viscosity/100°C / ASTM D 7042	13.3 mm ² /s
Viscosity index / ASTM D 2270	145

49720

02/2026-49720-41

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eisligen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de - Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited partnership Registered office Eisligen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH - Registered office Eisligen - Local Court Ulm HRB 530641



Flash point (Cleveland) / DIN ISO 2592	217 °C
Pour point / ASTM D 7346	-33°C
TBN	10.5 mgKOH/g

SPECIFICATION

API CI-4/SL; ACEA E7; Jaso DH-1; Global DHD-1

MANUFACTURER APPROVALS

DTFR 15B110; Volvo VDS-III; Renault RLD-2; MACK EO-N

Meet MAN M 3275-1 specification (obsolete)

Meets Caterpillar ECF-1A specification (self-certifying)

DIVINOL RECOMMENDATION

John Deere JDQ 78 A; MB 228.3; MB 229.1; Deutz DQC III-18; CNH MAT 3507; Cummins CES 20076, 20077, 20078; DDC 93215; Komatsu EO15W40DH; MTU Type 2; Valtra CR; Scania LDF; ZF-TE-ML 04P/07D

USE / APPLICATION

All-season oil, specifically for mixed vehicle fleets. Common fields of application of **Divinol Multimax Top 15W-40** are trucks and vehicles used in agriculture, forestry and construction industry. Also suitable for diesel or gasoline driven passenger cars according to stated ACEA/API level.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.