



Divinol Spezial 2000 HD SAE 50

HD Monograde oil SAE 50

ARTICLE DESCRIPTION

Monograde motor oil for wide application area. **Divinol Spezial 2000 HD SAE 50** has high reserves against wear and sludge. The product offers optimal lubrication as well as a very high oxidation stability even under difficult conditions.

TYPICAL KEY FIGURES

SAE Grade	50
Density/15°C / DIN EN ISO 12185	0.88 g/cm ³
Viscosity/100°C / ASTM D 7042	17 mm ² /s
Viscosity index / ASTM D 2270	142
Flash point (Cleveland) / DIN ISO 2592	230 °C
Pour point / ASTM D 7346	-24 °C
TBN	10 mgKOH/g

SPECIFICATION

49453

09/2025-49453-16

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eisingen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de - Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited partnership Registered office Eisingen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH - Registered office Eisingen - Local Court Ulm HRB 530641



API SJ/CF/CF-4

DIVINOL RECOMMENDATION

ACEA E1/E2; MB 227.0/228.1; MAN 270; Volvo VDS; ZF-TE-ML 02C; MTU Type 1; Cat TO-2

USE / APPLICATION

Monograde motor oil for wide application area. **Divinol Spezial 2000 HD SAE 50** has high reserves against wear and sludge. The product offers optimal lubrication as well as a very high oxidation stability even under difficult conditions.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.