ZELLER+GMELIN



TECHNICAL DATA SHEET

Divinol Special Oil HGB V-R

UTTO Oil SAE 10W-30

ARTICLE DESCRIPTION

Divinol Special Oil HGB V-R is a transmission/hydraulic oil (UTTO) for use in tractors as well as agricultural, forestry and construction machinery. The product offers optimum friction behavior and reduces brake noise. **Divinol Special Oil HGB V-R** protects against rust and corrosion and is compatible with conventional elastomers. In addition, the product offers very good low-temperature behavior and ensures excellent gear lubrication.

TYPICAL KEY FIGURES

Colour / DIN ISO 2049	L 4.0
SAE Grade	10W-30 / SAE 75W
Density/15°C / DIN EN ISO 12185	0.87 g/cm³
Viscosity/40°C / ASTM D 7042	65 mm²/s
Viscosity/100°C / ASTM D 7042	10.7 mm²/s
Viscosity index / ASTM D 2270	> 140
Flash point (Cleveland) / DIN ISO 2592	240°C
Pour point / ASTM D 7346	- 42 °C

SPECIFICATION

API GL-4/GL-5 low torque application, UTTO, HVLPD (DIN 51524 Part 2/3);

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eislingen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de - Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited partnership Registered office Eislingen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH - Registered office Eislingen - Local Court Ulm HRB 530641

DIVINOL RECOMMENDATION

SDFG OT 1891; Renault GA 12; Renault TH-FI; Allison C-4; Case MS 1204/1206/1207/1209/1210; Caterpillar TO-2; CNH MAT 3505/3506/3509/3525/3526; Valtra G02-08; Deutz-Allis AC Power Fluid 821 XL; IHC B5&B6 Hydran; Kubota UDT Fluid; Ford New Holland M2C48-C3/M2C86-B/M2C-134D; John Deere JDM J20 C/D; MF CMS M 1135/1141/1143/1145; New Holland NH410B/ NH420A; Volvo VME WB 101; Denison/Parker HF-0/HF-02; Eaton I-280-S/ M2950S; JCMAS HK P-041; White Q-1705/1722/1766/1766B/1802/1826; Oliver Type 55/5J/Q1802; Sauer/Danfoss Hydro Static Trans Fluid

Also applicable for Volvo WB 102 for half of the specified oil change interval. No "Low Viscosity" UTTO oil.

USE / APPLICATION

Divinol Special Oil HGB V-R can be used in tractors, agricultural and construction machinery as hydraulic oil, as transmission oil and as brake fluid for hydraulic tractor brakes.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eislingen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de - Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited partnership Registered office Eislingen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH - Registered office Eislingen - Local Court Ulm HRB 530641