ZELLER+GMELIN



TECHNICAL INFORMATION

Divinol Spezialöl HGB

STOU Tractoroil (also for tractor CVT use)

PRODUCT DESCRIPTION

All-purpose high-performance STOU oil for agricultural and forestry machinery. Especially suitable for agricultural tractors and construction equipment in engines, common oil circuit, transmission, CVT gears, final drives as well as in hydraulic systems. **Divinol Spezialöl HGB** can also be used as UTTO oil.

CHARACTERISTICS

SAE Grade	10W-30

SPECIFICATIONS

API CG-4/SF; API GL-4/GL-5 low torque application; ACEA E3; HVLPD (DIN 51524 Part 2/3); STOU / UTTO

APPROVALS

ZF TE-ML 06B/07B (ZF010463); MF CMS M 1145

DIVINOL RECOMMENDATION

Fendt Vario (CVT); ZF-TE-ML 06F; Steyr 397 88001; MF CMS M 1127/1139/1144; John Deere JDM J20C / JDM J27; IHC B6; CNH MAT 3525; Kubota UDT; Ford-New Holland 024C/324B/410B/420A/540B; New Holland NH82009201/2/3; Ford ESN-M2C-41B /86B&C -121E / -134D / -159C; Case MS 1209; Valtra Super; Deutz DQC I-02; JCB-Standard 4004/0300; Sperry Vickers/Eaton M2950S/ I-280-S; Sunstrand/ Danfoss Hydrostatic Trans Fluid; MB 227.1; MB 228.1; Allison C4; Caterpillar TO-2; FIAT AF 87; MAN 271; ZF TE-ML 06A/06C/06R/06F

APPLICATION

Engine, transmission and hydraulic oil for tractors, forestry and construction equipment as well as brake fluid for hydraulic brakes. The high viscosity index ensures an immediate response of the hydraulic systems (HLPD and HVLPD) even at low temperatures and high stresses. The friction coefficient was set to special requirements of the oil-bath "wet brakes", especially with non-asbestos brake pads and power shift clutches for auxilary drives.

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co. KG · Schlossstraße 20 · 73054 Eislingen/Fils · Germany · Phone: +49 7161 802-0 · info@zeller-gmelin.de · Managing Directors: Thomas Alpers, Dipl.-Ing. (FH) · Alexandra Scaglione, Dipl.-Betriebsw. (FH) · Dirk Eisele, Dr. rer. nat. · Tillmann Gehring, Dipl.-Ing. (FH), LL.M. · Limited Partnership, registered office in Eislingen · Ulm Local Court, HRA 530107 · General Partner: Zeller Gmelin Verwaltungs GmbH · Registered office in Eislingen · Ulm Local Court, HRB 530641