ZELLER+GMELIN



TECHNICAL DATA SHEET

Divinol Synthogear 75W

High quality gear oil for passenger cars and LCVs

ARTICLE DESCRIPTION

Divinol Synthogear 75W was formulated on the basis of HC synthesis technology and works with novel additive compounds to meet the demands of the material mix in modern transmissions of passager cars or LCVs. This gear oil is suitable for a large number of manual transmissions and dual-clutch transmissions, offers fuel-saving potential as well as optimum wear protection thanks to excellent shear stability. **Divinol Synthogear 75W** can be used in **hybrid vehicles**.

TYPICAL KEY FIGURES

Appearance	clear
SAE Grade	75W
Density/15°C / DIN EN ISO 12185	0.86 kg/m³
Viscosity/40°C / ASTM D 7042	54 mm²/s
Viscosity/100°C / ASTM D 7042	9.3 mm²/s
Viscosity index / ASTM D 2270	155
Flash point (Cleveland) / DIN ISO 2592	215 °C

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eislingen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de - Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited partnership Registered office Eislingen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH - Registered office Eislingen - Local Court Ulm HRB 530641

Pour point / ASTM D 7346	-42 °C

SPECIFICATION

API GL-4; MIL-L-2105

DIVINOL RECOMMENDATION

BMW MTF LT-2
BMW MTF LT-3
BMW MTF LT4
Ford WSD-M2C200-C
Ford WSS-M2C200-D2
FIAT MZ1
FIAT MZ6
FIAT MZ7
GM 1940182
GM 1940764
GM 1940768
MB 235.10
NISSAN MT-XZ
NISSAN MT-XZ TL (JR Type)
PSA B71 2330
PSA B71 2315
PSA B71 2316 (HBVFE)
PSA 9730 A8
Special gear oil, MTF 94
Special Honda MTF
Special Honda MTF-II
Special Honda MTF-III
Volvo 97308
Volvo 97309
VW G 009 317
VW G 052 171
VW G 052 178
VW G 052 512
VW G 052 527
VW G 052 726
VW G 060 726
VW G 50 (VW 501 50)

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eislingen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de - Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited partnership Registered office Eislingen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH - Registered office Eislingen - Local Court Ulm HRB 530641

VW GO 52 527
VW GO 70 726
Divinol Synthogear 75W can also be filled, where oils of the quality Tranself NFJ/ NFP/ TRJ/ TRT/ TRZ/ TRP/ TRX are required.

USE / APPLICATION

This modern formulation ensures optimum cleanliness in the gearbox. The miscibility with mineral HC synthesis products and synthetics for European and Asian models where oil with viscosity 75W is required can be assured. With **Divinol Synthogear 75W** a wide variety of cars can be filled, which are need a gear oil with viscosity 75 W.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eislingen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de - Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited partnership Registered office Eislingen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH - Registered office Eislingen - Local Court Ulm HRB 530641