



Divinol Syntholight 03 5W-30

High quality motor oil SAE 5W30 according ACEA C3

ARTICLE DESCRIPTION

High-performance engine oil on the basis of advanced technology known as third longlife generation of motor oil. Many passenger cars and light duty vehicles built by VW Group and other vehicle manufacturers can be filled with this engine oil. **Divinol Syntholight 03 5W-30** offers optimal lubricating safety over the entire maintenance interval period and is suitable for exhaust gas aftertreatment systems such as diesel particulate filters. The slightly lowered HTHS viscosity enables fuel savings and thus also contributes to protect the environment. **Divinol Syntholight 03 5W-30** can be used in vehicles with an automatic start-stop system.

TYPICAL KEY FIGURES

SAE Grade	5W-30
Density/15°C / DIN EN ISO 12185	0.85 g/cm ³
Viscosity/40°C / ASTM D 7042	63 mm ² /s
Viscosity/100°C / ASTM D 7042	11 mm ² /s

49251

10/2025-49251-31

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE. Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eisingen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de
- Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited partnership Registered office Eisingen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH - Registered office Eisingen - Local Court Ulm HRB 530641



Viscosity index / ASTM D 2270	167
Flash point (Cleveland) / DIN ISO 2592	210°C
Pour point / ASTM D 7346	<= -33°C
TBN	>= 6 mgKOH/g

SPECIFICATION

API SN; ACEA C2/C3

DIVINOL RECOMMENDATION

VW 504.00/507.00; MB 229.51; BMW Longlife-04 (2017); PSA B71 2297; FPW9.55535/03

USE / APPLICATION

Divinol Syntholight 03 5W-30 is ideal for portfolio reduction. Except for VW R5 and V10 engines produced before 2007.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.