



Divinol Syntholight 10W-60

High-Performance Oil for Powerful Engines

PRODUCT DESCRIPTION

Divinol Syntholight 10W-60 is a premium motor oil that has been specially developed for use in engines subjected to extreme thermal stress. The combination of fully synthetic base oil, high-quality synthetic oils, and premium additives results in an outstanding motor oil that can also be used in racing without any problems.

It is also suitable for use in motorcycles meeting the **JASO MA-2** specification.

Advantages:

- + Unique dispersion properties ensure excellent engine cleanliness
- + Outstanding cleaning properties for all engine components
- + Corrosion protection
- + Excellent anti-wear properties
- + Outstanding reliability of the lubricating film
- + Very high resistance to aging

1

KEY METRICS

Color / DIN ISO 2049	5
SAE class	10W-60
Density/15°C / DIN EN ISO 12185	0.850 g/cm ³
Ash / sulphate DIN 51575	0.9
Viscosity/40°C / ASTM D 7042	164 mm ² /s
Viscosity/100°C / ASTM D 7042	23 mm ² /s
Viscosity index / ASTM D 2270	≥ 165
Flash point (according to Cleveland) / DIN ISO 2592	≥ 220 °C
Pour point / ASTM D 7346	-39 °C

TBN

8.2 mgKOH/g

SPECIFICATIONS

API SL/CF; JASO MA-2

APPLICATION

High-performance engine oil suitable for use in gasoline and diesel engines, both turbocharged and non-turbocharged, such as in passenger cars, muscle cars, motorcycles, and older vehicles.

Take advantage of our service, we will be happy to advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.