



Divinol Syntholight 505.01 SAE 5W-40

Low Saps HC-Synthesis multigrade oil SAE 5W-40

ARTICLE DESCRIPTION

Divinol Syntholight 505.01 SAE 5W-40 is a low-friction engine oil based on HC synthesis technology, which is tailored to the requirements of the pump-nozzle diesel engine concept of VW TDI engines, among others. **Divinol Syntholight 505.01 SAE 5W-40** can be used in gasoline and diesel engines in accordance with the manufacturer's specifications. The oil is characterized by a new formulation concept. Low fuel consumption, high thermal stability, excellent cleaning properties and therefore less wear. Also suitable for LPG/CNG-powered engines. Keep to manufacturer's instructions!

1

TYPICAL KEY FIGURES

Density/15°C / DIN EN ISO 12185	0.85
Colour / Appearance	yellow-brown
Viscosity/40°C / DIN EN ISO 3104	80 mm ² /s
Viscosity/100°C / ASTM D 7042	13.2 mm ² /s
Viscosity index / ASTM D 2270	>= 170
Pour point / ASTM D 7346	-39
TBN	8.2 mgKOH/g

SPECIFICATION

ACEA C3; API SP



DIVINOL RECOMMENDATION

MB 229.51; MB 229.31; VW 505.00/505.01; BMW-Longlife 04; Ford WSS M2C-917-A; Fiat 9.55535-S2; Renault RN 0700/ 0710; GM Opel Dexos 2; GM-LL-A-025; GM-LL-B-025

USE / APPLICATION

For many cars with gasoline and diesel engines including turbochargers. The long VW maintenance interval extensions do not apply here!

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.