



TECHNICAL INFORMATION

Divinol Syntholight 5W-40

High-quality multigrade motor oil SAE 5W-40

PRODUCT DESCRIPTION

Divinol Syntholight 5W-40 is a low-friction engine oil based on state-of-the-art HC synthetic technology. It ensures maximum operational reliability, minimal wear, and measurable fuel savings by reducing friction losses, as well as excellent cold-start properties combined with very good pumpability. Natural oxidation stability and a balanced additive package with high reserves of active ingredients prevent the formation of black sludge in the oil.

CHARACTERISTICS

Colour / DIN ISO 2049	4
SAE Grade	5W40
Density/15°C / DIN EN ISO 12185	0.86 g/cm ³
Ash / Sulfate DIN 51575	0.9
Viscosity/40°C / ASTM D 7042	87 mm ² /s
Viscosity/100°C / ASTM D 7042	14.3 mm ² /s
Viscosity index / ASTM D 2270	172
Flash point (Cleveland) / DIN ISO 2592	>= 195 °C
Pour point / ASTM D 7346	-39 °C
TBN	10.8 mgKOH/g

SPECIFICATIONS

API SQ/CF; ACEA A3/B4

APPROVALS

MB Approval 229.3



DIVINOL RECOMMENDATION

Porsche A40; Renault RN 0700/0710; VW 502.00/505.00; GM-LL-A-025; GM-LL-B-025; BMW Longlife-01; FIAT 9.55535 N2; PSA B71 2296

APPLICATION

Divinol Syntholight 5W-40 is a high-performance, low-friction motor oil that has been specially designed for gasoline and diesel passenger car engines, both with and without turbochargers.

Take advantage of our service, we will be happy to advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.