



TECHNICAL DATA SHEET

Divinol Syntholight 5W-50

High performance 5W-50 for broad use

PRODUCT DESCRIPTION

Divinol Syntholight 5W-50 is a high-tech engine oil for the most demanding requirements. The use of quality base oils and the selected range of additives, ensures excellent protection against wear, deposits and corrosion. The product enables an optimal lubrication and flowability during cold start as well as in the low temperature range. Divinol Syntholight 5W-50 offers safe oil pressure even under extreme temperatures conditions and guarantees a longer engine life.

CHARACTERISTICS

Colour / DIN ISO 2049	3.5
SAE Grade	5W50
Density/15°C / DIN EN ISO 12185	0,850 g/cm ³
Ash / Sulfate DIN 51575	1 %
Viscosity/40°C / ASTM D 7042	115 mm ² /s
Viscosity/100°C / ASTM D 7042	18 mm ² /s
Viscosity index / ASTM D 2270	175
Flash point (Cleveland) / DIN ISO 2592	220 °C
Pour point / ASTM D 7346	-34 °C

49510

04/2025-49510-15

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Syntholight 5W-50

High performance 5W-50 for broad use

TBN

9 mgKOH/g

SPECIFICATION

ACEA A3/B4; API SN/CF

DIVINOL RECOMMENDATION

MB 229.3; VW 502 00 / 505 00; BMW Longlife 01 (<2019); Porsche A40

APPLICATION

High-tech engine oil for all Otto and Diesel engines including turbocharger. **Divinol Syntholight 5W-50** is also suitable for hydrostatic systems in e.g. lawn tractors.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49510

04/2025-49510-15

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.