ZELLER+GMELIN



TECHNICAL INFORMATION

Divinol Syntholight C2 0W-30

High-Tec 0W-30 according ACEA C2 formulated on HC base oil & PAO

PRODUCT DESCRIPTION

Divinol Syntholight C2 0W-30 is a smooth-running engine oil blended with high valuable additives, most advanced HC base oil technology and PAO. The product is recommended for Otto and Diesel engines where an engine oil according ACEA C2 is necessary. A lot of modern cars of PSA Group, Renault, Ford, Fiat, Honda, Mazda, Citroen are designed for `fuel efficiency` which need an oil like **Divinol Syntholight C2 0W-30.** This high-quality engine oil ensures fast lubrication in start and warm-up phases, significantly less engine wear and fuel savings, and thus better emission control. **Divinol Syntholight C2 0W-30** is a hybrid-ready engine oil **(H.E.V / P.E.H.V)** and can also be used in vehicles with an **automatic start-stop system**.

CHARACTERISTICS

SAE Grade	0W-30
Density/15°C / DIN EN ISO 12185	0.84 kg/m³
Viscosity/40°C / ASTM D 7042	55 mm²/s
Viscosity/100°C / ASTM D 7042	10.9 mm²/s
Viscosity index / ASTM D 2270	> 170
Flash point (Cleveland) / DIN ISO 2592	≥ 215 °C
Pour point / ASTM D 7346	- 36 °C
TBN	8 mgKOH/g

DIVINOL RECOMMENDATION

ACEA C2; MB 229.61; BMW LL 12-FE; PSA B712312; Ford WSS-M2C-950A; Iveco 18-1811 SC1 LV-16; Jaguar Land Rover STJLR.03.5007; Fiat 9.55535-S1; Fiat 9.55535-GS1; Fiat 9.55535-DS1; FPW9.55535/DH1 Renault*; Honda*; Mazda*; Citroen*; SsangYong*

*according service manual of OEM

APPLICATION

Divinol Syntholight C2 0W-30 guarantees a rapid oiling of the the engine even under low temperature conditions and offers a sufficiently thick lubricating film at higher temperatures.

Take advantage of our service, we will be happy to advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eislingen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de - Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited partnership Registered office Eislingen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH - Registered office Eislingen - Local Court Ulm HRB 530641