



Divinol Syntholight C2 5W-30

High-performance 5W-30, meeting ACEA C2 specifications

PRODUCT DESCRIPTION

Divinol Syntholight C2 5W-30 is a special HC synthetic oil for modern gasoline and diesel engines. The special "Fuel Economy" formulation helps reduce fuel consumption. This high-quality engine oil ensures rapid oil circulation, especially during startup and warm-up. **Divinol Syntholight C2 5W-30** is particularly suitable for vehicles from French and Asian manufacturers. Also suitable for LPG/CNG-powered engines. Follow the manufacturer's instructions!

KEY METRICS

SAE class	5W30
Density/15°C / DIN EN ISO 12185	0.834 g/cm ³
Viscosity/40°C / ASTM D 7042	70 mm ² /s
Viscosity/100°C / ASTM D 7042	12 mm ² /s
Viscosity index / ASTM D 2270	168
Flash point (according to Cleveland) / DIN ISO 2592	>= 180 °C
Pour point / ASTM D 7346	-42 °C
TBN	8.5 mgKOH/g

1

SPECIFICATIONS

API SQ; ACEA C2

DIVINOL RECOMMENDATION

Fiat 9.55535 S1, Iveco 18-1811 SC1, PSA B71 2288/PSA B71 2290 (<2017), PSA B71 2295, RN 0700, Citroën*, Toyota*, Honda*, Mazda*

*in accordance with the specifications in the owner's manual / service booklet



APPLICATION

Divinol Syntholight C2 5W-30 It is recommended for gasoline and diesel engines, in accordance with the respective manufacturers' specifications for, for example, Fiat, Toyota, Honda, and Mazda.



Take advantage of our service, we will be happy to advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.