



Divinol Syntholight FE 5W-20

Low-viscosity engine oil for petrol driven passenger cars

PRODUCT DESCRIPTION

Divinol Syntholight FE 5W-20 is a modern engine oil in the SAE 5W20 class. Thanks to its special additive components and base oils, Divinol Syntholight FE 5W-20 can be described as particularly fuel-efficient and emission-reducing. Of course, the product also ensures extremely rapid distribution of the engine oil throughout the engine, thereby significantly reducing cold-start wear when starting the engine. **Divinol Syntholight FE 5W-20** ensures optimal oil supply and the resulting lubrication reliability with regard to the oil film. Divinol Syntholight FE 5W-20 is a hybrid-ready engine oil (**H.E.V./P.E.H.V.**) and can also be used in vehicles with **automatic start-stop systems**.

Advantages:

- + Unique dispersion properties ensure excellent engine cleanliness
- + Excellent cleaning properties for all engine components
- + Corrosion protection
- + Excellent anti-wear properties
- + Outstanding reliability of the lubricating film
- + Very high resistance to aging
- + Saves fuel

1

KEY METRICS

Color / DIN ISO 2049	2
SAE class	5W-20
Density/15°C / DIN EN ISO 12185	0.85 g/cm ³
Ash / sulphate DIN 51575	0.9
Viscosity/40°C / ASTM D 7042	46 mm ² /s
Viscosity/100°C / ASTM D 7042	8.3 mm ² /s
Viscosity index / ASTM D 2270	160
Flash point (according to Cleveland) / DIN ISO 2592	>= 200 °C

Pour point / ASTM D 7346

$\leq -33\text{ }^{\circ}\text{C}$

TBN

6 mgKOH/g

SPECIFICATIONS

API SQ Plus; ILSAC GF 7A

DIVINOL RECOMMENDATION

DEXOS 1 Gen. 3; Chrysler MS-6395; Ford WSS-M2C-960-A1; Ford WSS-M2C-945-A1; GM 6094 M

APPLICATION

Divinol Syntholight FE 5W-20 is recommended for gasoline engines and electric hybrid vehicles, in accordance with the respective manufacturer's specifications.

Take advantage of our service, we will be happy to advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.