ZELLER+GMELIN



TECHNICAL INFORMATION

Divinol Syntholight LV 0W-20

Top-of-the-line SAE 0W20 engine oil

PRODUCT DESCRIPTION

Divinol Syntholight LV 0W-20 is an SAE 0W20 engine oil designed specifically for modern engines that operate in a resource-efficient manner. **Divinol Syntholight LV 0W-20** is ideally suited for ensuring a long engine service life (including turbochargers), despite its low-viscosity SAE Class 0W20 rating. Due to the oil's formulation, there are no adverse effects on downstream systems such as exhaust aftertreatment. The high-quality base oils, combined with top-level additive technology, provide excellent oil flow properties—particularly at both low and high temperatures—along with optimal protection against wear and deposits. **Divinol Syntholight LV 0W-20 is** a hybrid-ready engine oil **(H.E.V./P.E.H.V.)** and can also be used in vehicles with **automatic start-stop systems**.

Advantages:

+ ideal for low-temperature applications
+ low oil consumption
+ Suitable even for fuels with an ethanol content of up to E85
+ Optimal protection for the engine and its components
+ Saves fuel

1

CHARACTERISTICS

Colour / DIN ISO 2049	3
SAE Grade	0W20
Density/15°C / DIN EN ISO 12185	0.84 g/cm³
Viscosity/40°C / ASTM D 7042	45.2
Viscosity/100°C / ASTM D 7042	8.5
Viscosity index / ASTM D 2270	168
Flash point (Cleveland) / DIN ISO 2592	220 °C
Pour point / ASTM D 7346	-42 °C
TBN	7.4

SPECIFICATIONS

API SQ; ILSAC GF 7A

DIVINOL RECOMMENDATION

DEXOS 1 Gen. 3; GM 6094M; Chrysler MS-6395; Ford WSS-M2C-962-A1; Ford WSS-M2C947-A; Ford WSS-M2C947-B1; Subaru*

*in accordance with the specifications in the owner’s manual / service manual

APPLICATION

Suitable for use in gasoline and diesel engines, with or without turbocharging, such as in passenger cars, delivery vans, and minibuses. The product is ideally suited for vehicles equipped with exhaust aftertreatment systems. Fuel savings, especially on short trips and in stop-and-go traffic, can be achieved with Divinol Syntholight LV 0W-20.

Take advantage of our service, we will be happy to advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eislingen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de - Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited partnership Registered office Eislingen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH - Registered office Eislingen - Local Court Ulm HRB 530641