



TECHNICAL DATA SHEET

Divinol Syntholight R 5W-30

Suitable for Renault RN 0720

PRODUCT DESCRIPTION

Divinol Syntholight R 5W-30 is a special HC synthesis oil for modern petrol and diesel engines with low ash content. This quality motor oil provides fast lubrication, especially in start and warm-up phase. Various Renault models need this special motor oil RN 0720 which is well suited for exhaust-aftertreatment-systems/ diesel particulate filters. **Divinol Syntholight R 5W-30** can also be deployed in LPG/CNG motors (according OEM information).

CHARACTERISTICS

SAE Grade	5W-30
Density/15°C / DIN EN ISO 12185	0,850 g/cm ³
Ash / Sulfate DIN 51575	0.5 %
Viscosity/40°C / ASTM D 7042	68 mm ² /s
Viscosity/100°C / ASTM D 7042	12 mm ² /s
Viscosity index / ASTM D 2270	>170
Flash point (Cleveland) / DIN ISO 2592	>210°C
Pour point / ASTM D 7346	<-36°C
TBN	6.7 mgKOH/g

SPECIFICATION

49350

01/2024-49350-26

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Syntholight R 5W-30

Suitable for Renault RN 0720

ACEA C4

MANUFACTURER APPROVAL

Renault RN 0720

DIVINOL RECOMMENDATION

Renault RN 0720; MB 226.51; Fiat 9.55535-S4

APPLICATION

Divinol Syntholight R 5W-30 is recommended for gasoline and diesel engines (also LPG/CNG) in compliance with manufacturer's instructions, especially for french cars with exhaust aftertreatment system.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49350

01/2024-49350-26

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.