ZELLER+GMELIN



TECHNICAL INFORMATION

Divinol Syntholight Top 5W-40

Premium HC-Synthesis Multigrade Oil SAE 5W-40

PRODUCT DESCRIPTION

Divinol Syntholight Top 5W-40 is a low-friction engine oil produced using state-of-the-art synthetic technology. It ensures maximum operational reliability, minimal wear, and fuel savings by reducing friction losses, as well as excellent cold-start properties combined with very good pumpability. The combination of various base oils with a high-quality additive package results in an outstanding engine oil. Natural oxidation stability and a balanced additive formulation with high reserves of active ingredients prevent the formation of black sludge.

Advantages:

+ Unique dispersion properties ensure excellent engine cleanliness
+ Excellent cleaning properties for all engine components
+ Corrosion protection
+ Excellent anti-wear properties
+ Outstanding reliability of the lubricating film
+ Very high resistance to aging

KEY METRICS

Color / DIN ISO 2049	L 4.0
SAE class	5W-40
Density/15°C / DIN EN ISO 12185	0.850 g/cm³
Ash / sulphate DIN 51575	1.2
Viscosity/40°C / ASTM D 7042	88 mm²/s
Viscosity/100°C / ASTM D 7042	14.9 mm²/s
Viscosity index / ASTM D 2270	172
Flash point (according to Cleveland) / DIN ISO 2592	230 °C
Pour point / ASTM D 7346	-36 °C

TBN	>= 10 mg KOH/g

SPECIFICATIONS

API SQ/CF; ACEA A3/B4

APPROVALS

MB Approval 229.5

DIVINOL RECOMMENDATION

MB 226.5; BMW Longlife-01 (<2019); Fiat 9.55535-M2; GM-LL-A-025; GM-LL-B-025; Porsche A40; PSA B71 2296; Renault RN 0700/0710; VW 505.00/502.00

APPLICATION

Divinol Syntholight Top 5W-40 is a high-performance, low-friction motor oil that has been specially designed for gasoline and diesel passenger car engines, both with and without turbochargers.

Take advantage of our service, we will be happy to advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

The information contained in this document (the "product specification") is based on our current knowledge. It does not exempt the processor or user from carrying out their own tests. Properties of the product that go beyond the above information and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing statutory provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional statutory objective quality requirements is not owed. By ordering our product without objection and with knowledge of this product specification, you hereby declare your agreement.

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co KG - Schlossstraße 20 - 73054 Eislingen/Fils - Germany - Phone: +49 7161 802-0 - info@zeller-gmelin.de - Managing Directors: Dipl.-Ing. (FH) Siegfried Müller - Dipl.-Betriebsw. Alexandra Scaglione - Dipl.-Ing. (FH) Thomas Alpers - Limited partnership Registered office Eislingen - Local Court Ulm HRA 530107 - Personally liable partner Zeller+Gmelin Verwaltungs GmbH - Registered office Eislingen - Local Court Ulm HRB 530641