



Divinol Syntholight WV 0W-20

Modern 0W-20 Engine Oil, Compliant with VW 508.00/509.00

PRODUCT DESCRIPTION

Divinol Syntholight WV 0W-20 is a high-performance engine oil based on polyalphaolefins (PAO), which can be used in the latest engines of the VW Group (VW, Audi, Skoda, Seat) as well as for Porsche. With this lubricant, it is particularly important to emphasize that emission reduction systems are optimally supported and savings in fuel consumption can be achieved. In addition, **Divinol Syntholight WV 0W-20** is particularly suitable for outstanding engine cleanliness, wear protection and long engine life. Considerable fuel savings are achieved by using the extremely low viscosity grade SAE 0W-20. **Divinol Syntholight WV 0W-20** is a **hybrid-ready engine oil (H.E.V / P.E.H.V)** and can also be used in vehicles with automatic start-stop systems.

The **Divinol Syntholight WV 0W-20** can be used in the latest VW Group engines of the following types:

- + 3.0/2.0/1.5/1.4/1.2/1.0 TSI/TFSI/MPI
- + 25/30/35/40/45/55 TFSI
- + 3.0 TDI
- + E-hybrid vehicles

KEY METRICS

SAE class	0W-20
Density/15°C / DIN EN ISO 12185	0.83 g/cm ³
Color / Appearance	green
Viscosity/40°C / ASTM D 7042	40 mm ² /s
Viscosity/100°C / ASTM D 7042	8.2 mm ² /s
Viscosity index / ASTM D 2270	184
Flash point (according to Cleveland) / DIN ISO 2592	> 200°C
Pour point / ASTM D 7346	-48 °C
TBN	8.2 mgKOH/g



SPECIFICATIONS

ACEA C5

APPROVALS

VW 508.00/509.00

DIVINOL RECOMMENDATION

Porsche C20

APPLICATION

Divinol Syntholight WV 0W-20 keeps the engine clean and powerful, with significantly lower fuel consumption and CO2 emissions. When cold starting, the excellent fluidity at low temperatures is suitable for minimizing cold wear.

ATTENTION: Divinol Syntholight WV 0W-20 must not be filled in vehicles that require VW standard 504.00/507.00.

Take advantage of our service, we will be happy to advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.